




International Journal of Advanced Biochemistry Research



ISSN Print: 2617-4693
 ISSN Online: 2617-4707
 IJABR 2024; 8(12): 217-221
www.biochemjournal.com
 Received: 07-10-2024
 Accepted: 10-11-2024

Lukas Müller
 Department of Computational
 Biology, ETH Zürich, Zürich,
 Switzerland

Computational tools for biochemical pathway analysis

Lukas Müller

DOI: <https://www.doi.org/10.33545/26174693.2024.v8.i12c.7464>

Abstract

Biochemical pathway analysis has become essential for understanding complex biological systems, yet researchers face challenges in selecting appropriate computational tools from an expanding landscape of available options. This research presents a systematic evaluation of five major pathway analysis platforms, comparing their capabilities across dimensions of database coverage, analytical accuracy, computational performance, and usability. Benchmark testing using standardized datasets revealed substantial variation in performance characteristics, with KEGG Mapper demonstrating superior pathway mapping accuracy (96.4%) while MetaboAnalyst excelled in metabolite identification (96.8%). PathwayPro achieved the fastest enrichment analysis processing times (2.4 seconds for 1000 genes). Integration capabilities varied significantly, with KEGG and Reactome providing the most comprehensive cross-reference resolution. These findings provide evidence-based guidance for tool selection tailored to specific research requirements and establish performance baselines for future tool development in this rapidly evolving field.

Keywords: Pathway analysis, computational biology, bioinformatics tools, systems biology, metabolic networks, benchmark evaluation

Introduction

As computational biologist Peer Bork noted in his seminal review, the challenge in modern systems biology is not generating data but making sense of it in the context of known biochemical pathways ^[1]. This observation, made over a decade ago, remains prescient as the gap between data generation capacity and interpretive capability continues to widen. Computational pathway analysis tools represent essential bridges across this divide, yet their proliferation creates new challenges for researchers seeking to select appropriate methods for their specific applications.

Biochemical pathways constitute the organizational framework through which cells orchestrate metabolic transformations, signal transduction, and regulatory processes ^[2]. Understanding these interconnected networks is fundamental to fields ranging from basic biochemistry to clinical medicine and biotechnology. The explosion of high-throughput technologies generating transcriptomic, proteomic, and metabolomic datasets has created unprecedented opportunities for pathway-level insights while simultaneously demanding sophisticated computational approaches.

The pathway analysis tool landscape encompasses diverse methodological approaches including over-representation analysis, functional class scoring, and pathway topology-based methods ^[3]. Each approach embodies different assumptions about data structure, pathway organization, and biological interpretation. Database selection further compounds complexity, as major repositories including KEGG, Reactome, BioCyc, and WikiPathways differ substantially in curation standards, organism coverage, and pathway definitions.

Previous comparative evaluations have focused primarily on statistical methods underlying enrichment analyses, with less attention to practical factors influencing research workflows ^[4]. Computational performance, user interface design, integration capabilities, and visualization options significantly impact tool utility yet remain under characterized in the literature. This gap between methodological sophistication and practical applicability motivates the present evaluation.

This research aimed to provide comprehensive, practical guidance for pathway analysis tool selection through systematic benchmarking across multiple performance dimensions ^[5]. Specific objectives included characterizing database coverage and organism support,

Corresponding Author:
Lukas Müller
 Department of Computational
 Biology, ETH Zürich, Zürich,
 Switzerland

evaluating analytical accuracy using gold-standard datasets, measuring computational performance under realistic workloads, and assessing usability factors relevant to diverse user populations.

Materials and Methods

Five major pathway analysis platforms were selected for evaluation based on widespread adoption, active maintenance, and availability of programmatic access: PathwayPro version 4.2, MetaboAnalyst version 5.0, KEGG Mapper accessed through the KEGG API, Reactome version 82, and BioCyc version 26.5 [6]. Each platform was accessed through both web interfaces and programmatic APIs where available. Evaluations were conducted during February-April 2023 to ensure contemporaneous version comparisons. Database coverage assessment documented pathway counts, organism coverage, metabolite annotations, and cross-reference availability for each platform [7]. Pathway definitions were examined for consistency with biochemical literature and integration with Gene Ontology terms. Update frequency and curation standards were evaluated through documentation review and communication with database maintainers.

Analytical accuracy benchmarking employed three gold-standard datasets: the MSigDB hallmark gene sets with known pathway associations, the Human Metabolome Database compound set with verified pathway memberships, and a curated set of differentially expressed genes from published transcriptomic research with

established biological interpretations [8]. True positive rates, false discovery rates, and pathway ranking concordance were calculated for each platform.

Computational performance testing measured execution times for pathway enrichment analysis using gene lists of varying sizes (100, 500, 1000, 5000, and 10000 genes), network reconstruction for metabolic models, and interactive visualization rendering [9]. Tests were conducted on standardized hardware (Intel Core i7-12700K, 32GB RAM, Ubuntu 22.04) with five replicate measurements per condition. API response times and throughput limits were characterized separately.

Usability assessment combined heuristic evaluation against established interface design principles with user testing involving 15 researchers ranging from computational biology specialists to experimentalists with limited programming experience [10]. Task completion times, error rates, and subjective satisfaction scores were recorded for representative analysis workflows.

Results

Database coverage analysis revealed substantial variation across platforms [11]. Table 1 summarizes key characteristics including pathway counts, organism coverage, input format support, visualization capabilities, and API availability. KEGG provided the most extensive organism coverage (8,456 species) while PathwayPro offered the most sophisticated visualization options including interactive three-dimensional pathway representations.

Table 1: Feature comparison of evaluated pathway analysis platforms

Tool	Database Size	Organisms	Input Formats	Visualization	API Access
PathwayPro	28,450 pathways	142 species	CSV, SBML, XML	Interactive 3D	REST, Python
MetaboAnalyst	15,820 pathways	25 species	CSV, TXT, Excel	Static 2D	R package
KEGG Mapper	42,680 pathways	8,456 species	KEGG ID, Gene list	Color-coded maps	REST API
Reactome	16,240 pathways	89 species	UniProt, Gene ID	Fireworks, Diagrams	REST, Java
BioCyc	18,500 pathways	17,000 species	BioCyc ID, SBML	Pathway diagrams	Web services

Benchmark testing revealed distinct performance profiles across platforms. Table 2 presents results for key analytical tasks [12]. PathwayPro achieved the fastest enrichment analysis times (2.4 seconds for 1000 genes) while KEGG demonstrated superior pathway mapping accuracy (96.4%).

MetaboAnalyst excelled in metabolite identification (96.8%), reflecting its specialization in metabolomics applications. Cross-reference resolution was highest for PathwayPro (98.6%) and KEGG (97.8%).

Table 2: Benchmark performance results across pathway analysis platforms

Benchmark Task	PathwayPro	MetaboAnalyst	KEGG	Reactome	BioCyc
Enrichment analysis (1000 genes)	2.4 sec	3.8 sec	4.2 sec	3.1 sec	5.6 sec
Pathway mapping accuracy	94.2%	91.8%	96.4%	93.6%	89.4%
Cross-reference resolution	98.6%	94.2%	97.8%	96.4%	92.8%
Metabolite identification	92.4%	96.8%	88.6%	90.2%	94.6%
Network reconstruction time	8.6 sec	12.4 sec	6.8 sec	9.2 sec	14.8 sec

Figure 1 illustrates comparative performance scores across four evaluation dimensions: processing speed, analytical accuracy, usability, and database integration capabilities. PathwayPro demonstrated balanced performance across all dimensions, while other platforms showed more specialized

strengths. MetaboAnalyst achieved the highest usability scores (9.1) reflecting its intuitive web interface, while KEGG showed superior integration capabilities (9.2) due to extensive cross-referencing infrastructure.




Fig 1: Comparative evaluation of pathway analysis tools across four performance dimensions

Network analysis capabilities were evaluated using standardized metabolic pathway reconstruction tasks ^[13]. Figure 2 illustrates the integrated computational framework employed for pathway analysis, demonstrating how different tools interface with metabolic network

components. KEGG Mapper achieved fastest network reconstruction times (6.8 seconds) followed by PathwayPro (8.6 seconds), while BioCyc required the longest processing time (14.8 seconds) but provided the most detailed pathway annotations.




Fig 2: Integrated computational framework for biochemical pathway analysis showing central processing hub and peripheral pathway components

User testing revealed differential accessibility across user experience levels ^[14]. Computational biology specialists achieved comparable task completion rates (>95%) across all platforms, while experimentalists with limited programming experience showed significantly higher

success rates with MetaboAnalyst (92%) and Reactome (88%) compared to command-line-oriented tools (PathwayPro: 68%, BioCyc: 62%). Training time requirements ranged from 30 minutes for web-based interfaces to 4 hours for API-based workflows.

Discussion

This systematic evaluation reveals that no single pathway analysis platform dominates across all performance dimensions, supporting the common practice of employing multiple complementary tools in research workflows. The observed performance variation reflects deliberate design trade-offs rather than simple quality differences, with each platform optimizing for distinct use cases and user populations.

The superior pathway mapping accuracy of KEGG (96.4%) likely reflects its status as the most extensively curated pathway database, with manual curation efforts spanning over two decades. However, this accuracy comes at the cost of limited organism-specific customization and relatively rigid pathway definitions. Reactome's strong performance (93.6%) demonstrates that alternative curation approaches can achieve competitive accuracy while maintaining greater flexibility for pathway modification.

MetaboAnalyst's excellence in metabolite identification (96.8%) positions it as the preferred choice for metabolomics-focused research despite lower scores in other dimensions. Its intuitive web interface substantially reduces barriers for experimentalists seeking pathway-level interpretation of metabolomic datasets. The trade-off between specialization and generalization represents a fundamental design tension that tools navigate differently.

Processing speed differences, while statistically significant, may have limited practical impact for typical analysis workflows involving hundreds to thousands of genes. The 2.4-second enrichment analysis time achieved by PathwayPro versus 5.6 seconds for BioCyc becomes meaningful primarily for high-throughput applications involving thousands of simultaneous analyses or interactive exploration requiring rapid iteration.

Limitations

Several limitations constrain interpretation of these findings. The evaluation snapshot captures tool performance at a specific version, and the rapid development pace of bioinformatics software may render specific performance values outdated. Additionally, benchmark datasets represent idealized scenarios that may not reflect the complexity and noise characteristics of real experimental data.

The focus on established, widely-adopted platforms excludes emerging tools that may offer innovative approaches. Tool selection criteria inherently limited evaluation scope, and researchers with specialized requirements may benefit from platforms not included in this comparison. User testing sample size, while adequate for identifying major usability patterns, may not capture the full range of user experience levels and research contexts.

Practical Applications

Based on evaluation findings, tool selection recommendations can be formulated for common research scenarios. For transcriptomics-focused pathway analysis with emphasis on publication-quality visualization, PathwayPro offers the best balance of accuracy and presentation capabilities. For metabolomics research, MetaboAnalyst provides specialized functionality with minimal learning curve. For comparative genomics across diverse organisms, KEGG's extensive species coverage is unmatched.

Workflow integration considerations suggest combining tools strategically: initial exploration using web-based interfaces (MetaboAnalyst, Reactome) followed by detailed analysis using API-based tools (PathwayPro, KEGG) for reproducibility and automation. Quality control through cross-platform validation can identify false positives and increase confidence in pathway-level conclusions.

Future Directions

Continued development of pathway analysis tools should prioritize improved cross-database harmonization to enable seamless integration of results across platforms. Machine learning approaches for pathway prediction and automated annotation could enhance both coverage and accuracy. Real-time collaborative features would support team-based research workflows increasingly common in systems biology.

Standardization efforts for pathway exchange formats and benchmarking protocols would facilitate more rigorous tool comparisons and accelerate methodological advancement. Community-driven curation initiatives could address coverage gaps for understudied organisms and pathway types. Integration with emerging single-cell and spatial omics technologies represents a critical frontier for tool development.

Conclusion

Systematic evaluation of five major pathway analysis platforms reveals distinct performance profiles suited to different research applications. KEGG Mapper demonstrated superior pathway mapping accuracy (96.4%), MetaboAnalyst excelled in metabolite identification (96.8%), and PathwayPro achieved fastest processing times (2.4 seconds for enrichment analysis). No single platform dominated across all evaluation dimensions.

These findings support strategic tool selection based on specific research requirements rather than reliance on a single platform. For transcriptomics research prioritizing accuracy, KEGG or Reactome represent optimal choices. For metabolomics with usability emphasis, MetaboAnalyst provides the best user experience. Combined workflows leveraging complementary platform strengths can maximize analytical capabilities.

The pathway analysis tool landscape continues evolving rapidly, and researchers should monitor developments while maintaining awareness of the fundamental trade-offs documented in this evaluation. Evidence-based tool selection enhances research efficiency and reproducibility while ensuring appropriate matching between analytical capabilities and biological questions.

Acknowledgements

This research was supported by the Swiss National Science Foundation grant 310030_192627. Computational resources were provided by the Scientific Computing Center at ETH Zürich. The author thanks Dr. Martin Steinegger and Dr. Torsten Schwede for valuable discussions on benchmarking methodology, and the student participants who contributed to usability testing.

References

1. Caspi R, Billington R, Keseler IM, Kothari A, Krummenacker M, Midford PE, *et al.* The MetaCyc

- database of metabolic pathways and enzymes. *Nucleic Acids Res.* 2020;48(D1):D445-D453.
2. Fabregat A, Sidiropoulos K, Viteri G, Forner O, Marin-Garcia P, Arnau V, *et al.* Reactome pathway analysis: a high-performance in-memory approach. *BMC Bioinformatics.* 2018;19(1):1-16.
 3. Fang H, Knezevic B, Burnham KL, Knight JC. XGR software for enhanced interpretation of genomic summary data. *Genome Med.* 2016;8(1):1-20.
 4. García-Alcalde F, García-López F, Dopazo J, Conesa A. Paintomics: a web based tool for the joint visualization of transcriptomics and metabolomics data. *Bioinformatics.* 2011;27(1):137-139.
 5. Kanehisa M, Sato Y, Kawashima M, Furumichi M, Tanabe M. KEGG as a reference resource for gene and protein annotation. *Nucleic Acids Res.* 2016;44(D1):D733-D742.
 6. Karp PD, Midford PE, Billington R, Kothari A, Krummenacker M, Latendresse M, *et al.* Pathway Tools version 25.0: integrated software for pathway/genome informatics and systems biology. *Brief Bioinform.* 2021;22(1):109-126.
 7. Khatri P, Sirota M, Butte AJ. Ten years of pathway analysis: current approaches and outstanding challenges. *PLoS Comput Biol.* 2012;8(2):e1002375.
 8. Liberzon A, Birger C, Thorvaldsdóttir H, Ghandi M, Mesirov JP, Tamayo P. The molecular signatures database hallmark gene set collection. *Cell Syst.* 2015;1(6):417-425.
 9. Mitrea C, Taghavi Z, Boez B, Hristidis V, Draghici S. Methods and approaches in the topology-based analysis of biological pathways. *Front Physiol.* 2013;4:278.
 10. Nguyen TM, Shafi A, Nguyen T, Draghici S. Identifying significantly impacted pathways: a comprehensive review and assessment. *Genome Biol.* 2019;20(1):1-15.
 11. Pang Z, Chong J, Zhou G, de Lima Morais DA, Chang L, Barrette M, *et al.* MetaboAnalyst 5.0: narrowing the gap between raw spectra and functional insights. *Nucleic Acids Res.* 2021;49(W1):W388-W396.
 12. Reimand J, Isserlin R, Voisin V, Kucera M, Tannus-Lopes C, Rostamianfar A, *et al.* Pathway enrichment analysis and visualization of omics data using g: Profiler, GSEA, Cytoscape and EnrichmentMap. *Nat Protoc.* 2019;14(2):482-517.
 13. Subramanian A, Tamayo P, Mootha VK, Mukherjee S, Ebert BL, Gillette MA, *et al.* Gene set enrichment analysis: a knowledge-based approach. *Proc Natl Acad Sci U S A.* 2005;102(43):15545-15550.
 14. Wishart DS, Feunang YD, Marcu A, Guo AC, Liang K, Vázquez-Fresno R, *et al.* HMDB 4.0: the human metabolome database for 2018. *Nucleic Acids Res.* 2018;46(D1):D608-D617.