



International Journal of Veterinary Sciences and Animal Husbandry



ISSN: 2456-2912

NAAS Rating (2026): 4.61

VET 2026; 11(2): 360-364

© 2026 VET

www.veterinarypaper.com

Received: 03-12-2025

Accepted: 17-01-2026

Dr. Kiran Shinde

PhD Scholar, Division of Animal
Nutrition, ICAR-Indian
Veterinary Research Institute
Izzatnagar, Bareilly, Uttar
Pradesh, India

Dr. Suhana Parvin Muquit

PhD Scholar, Division of
Physiology & Climatology
ICAR-Indian Veterinary
Research Institute, Izzatnagar,
Bareilly, Uttar Pradesh, India

Dr. Chandrakant Kale

PhD Scholar, Division of
Veterinary Parasitology
Nagpur Veterinary College
Nagpur, Maharashtra, India

Corresponding Author:

Dr. Kiran Shinde

PhD Scholar, Division of Animal
Nutrition, ICAR-Indian
Veterinary Research Institute
Izzatnagar, Bareilly, Uttar
Pradesh, India

Advances in rumen sensors for real time assessment of metabolic processes

Kiran Shinde, Suhana Parvin Muquit and Chandrakant Kale

DOI: <https://www.doi.org/10.22271/veterinary.2026.v11.i2c.3037>

Abstract

The rumen is a highly dynamic, microbially driven bioreactor that underpins global ruminant productivity, yet its complex metabolic processes have historically been studied using invasive, intermittent, and labor-intensive methods. The emergence of rumen sensor technologies marks a paradigm shift from episodic measurement to continuous, real-time physiological intelligence. This review synthesizes recent advances in ingestible and implantable rumen sensors capable of monitoring pH, temperature, motility, redox potential, volatile fatty acids, and metabolic biomarkers. We critically examine innovations in wireless telemetry, biosensing platforms, microelectronics, and data integration frameworks that are transforming rumen health assessment and precision nutrition. Particular emphasis is placed on electrochemical and biosensor-based approaches for *in situ* metabolite detection, enabling early diagnosis of metabolic disorders such as subacute ruminal acidosis. Despite rapid technological progress, challenges persist in long-term stability, calibration drift, biocompatibility, power efficiency, and cost-effectiveness. By integrating sensor-derived data with precision livestock farming systems and predictive analytics, rumen monitoring technologies hold the potential to revolutionize herd management, improve animal welfare, and enhance sustainable ruminant production. This review outlines current capabilities, limitations, and future directions toward fully autonomous, data-driven rumen management systems.

Keywords: Rumen sensors, precision livestock farming, real-time rumen monitoring, electrochemical biosensors, volatile fatty acids (VFA) detection

1. Introduction

The accelerating growth of the global population has placed unprecedented pressure on livestock systems to produce more food with fewer resources. FAO projections estimate that by 2050, global meat demand will rise by 73% and dairy demand by 58% compared to 2011 levels, an increase that demands productivity gains without compromising environmental sustainability. Precision feeding and management technologies have therefore become central to modern ruminant agriculture. At the heart of this system lies the rumen: a highly specialized anaerobic bioreactor that enables ruminants to transform low-quality fibrous feeds into nutrient-dense, human-edible protein. Decades of research using fistulated animals have greatly expanded our understanding of rumen fermentation, microbial ecology, digestion, and diet-health interactions.

Yet traditional fistulation methods pose ethical and practical limitations. Surgical intervention, oxygen exposure, and altered rumen fluid dynamics can disrupt the native anaerobic ecosystem, potentially influencing microbial behavior and fermentation outcomes. Although alternative techniques such as ruminocentesis and oro-ruminal sampling offer partial solutions, they remain invasive or episodic. The need for minimally disruptive, physiologically relevant monitoring tools has therefore intensified.

Recent advances in precision livestock technologies have introduced ingestible and standalone rumen sensors capable of continuously tracking parameters such as pH, temperature, rumination, and activity. Since the early 2000s, these systems have evolved rapidly, enabling real-time assessment of metabolic status and early detection of disorders. However, challenges related to cost, durability, data integration, and large-scale adoption persist. Sustainable ruminant production now hinges on multidisciplinary innovation integrating microbiology,

nutrition, engineering, and data science to develop accurate, non-invasive monitoring systems that safeguard animal welfare while enhancing efficiency. The future of livestock production will depend not only on understanding the rumen, but on monitoring it intelligently and ethically in real time.

2. Rumen Sensors

2.1 Rumen sensors: Design, components, and functional principles

Rumen sensors are advanced bio-monitoring devices engineered to function within one of the most complex anaerobic ecosystems in nature, the rumen [2]. These devices detect and quantify biological and chemical parameters by converting physiological changes into measurable electronic signals proportional to specific analyte concentrations. In practical terms, they transform rumen physiology into actionable data. Contemporary rumen sensors enable continuous monitoring of pH, temperature, gas production, water intake, rumination patterns, and overall activity, providing a dynamic window into metabolic status. Importantly, they facilitate early detection of disorders such as subacute ruminal acidosis, digestive dysfunction, and even systemic conditions like mastitis, thereby supporting proactive herd management.

Most rumen sensors are administered orally using a balling gun, after which the bolus settles in the reticulorumen, where it remains for long-term monitoring. The procedure is minimally invasive, rapid, and safe when performed with basic training, making on-farm deployment practical and scalable.

2.2 Core components of rumen sensor systems

A typical rumen sensor system integrates several critical components [3]:

- **Probe/sensing unit:** The functional core of the device, housing one or multiple sensors capable of detecting pH, temperature, pressure, motility, or gas concentrations directly within the rumen environment.
- **Data logger:** An embedded recording system that captures and stores sensor outputs either continuously or at programmed intervals. Advanced systems support real-time data streaming.
- **Power source:** Internal batteries or rechargeable cells designed to withstand the rumen's harsh, anaerobic conditions while ensuring sustained operation.
- **Communication module:** Wireless transmission units (Bluetooth, radio frequency, Wi-Fi, or low-power wide-area networks) that relay data to external receivers, farm servers, or cloud-based analytical platforms.

2.3 Working principle

The operation of rumen sensors follows a systematic sequence [4]:

- **Placement:** Following oral administration, the sensor bolus lodges within the reticulorumen for continuous monitoring.
- **Detection:** Embedded sensing elements measure physiological and biochemical parameters in real time (e.g., pH electrodes detect acidity shifts; thermistors record temperature fluctuations).
- **Data acquisition:** Measured signals are processed and stored within the onboard data logger.
- **Transmission:** Data are periodically or continuously transmitted wirelessly to external systems for remote access.

- **Interpretation and intervention:** Analytical platforms convert raw data into health indicators, enabling early detection of deviations such as declining pH associated with subacute ruminal acidosis. This allows timely dietary modification, therapeutic intervention, and precision nutritional management.

By converting rumen dynamics into continuous digital intelligence, these systems represent a decisive step toward data-driven, welfare-conscious, and metabolically informed ruminant production.

3. Types of rumen sensors

- pH Sensors
- Temperature Sensors
- Biomarker Sensors
- Motility Sensors
- Metabolite Sensors
- Gas and Redox Sensors (Emerging approaches)

The rumen is also a major site of anaerobic gas production, particularly methane and carbon dioxide. Monitoring gas profiles and oxidation-reduction (redox) potential can provide valuable information about microbial activity, fermentation balance, and environmental sustainability. Although still largely in the experimental stage, integrated gas and redox sensors hold promise for linking rumen metabolism with greenhouse gas mitigation strategies.

3.1 pH sensors

Rumen pH sensors are designed to continuously measure acidity within the rumen, a critical determinant of digestive efficiency and animal health in ruminants such as cattle, sheep, and goats. Maintaining optimal rumen pH is essential for effective fiber fermentation and prevention of disorders such as subacute ruminal acidosis (SARA). These sensors are typically placed directly in the rumen as bolus devices, enabling real-time monitoring and early detection of pH fluctuations. The data support timely dietary and management interventions [5].

Most commercial rumen pH boluses use glass membrane electrode-based systems. While reliable, these electrodes are bulky, fragile, slow in response, difficult to miniaturize, and require frequent calibration and maintenance. To overcome these limitations, miniaturized solid-state sensors are being developed for long-term, wireless monitoring:

- **Potentiometric sensors:** Compact, fast-response sensors consisting of a working electrode and a reference electrode. Advances in micro- and nanofabrication have enabled solid-state versions suitable for rumen applications [6].
- **ISFET (Ion-sensitive field-effect transistor) Sensors:** These sensors measure pH using an ion-sensitive membrane coupled with transistor-based field sensing. Although small and robust, they require protective encapsulation for *in vivo* use.
- **EGFET (Extended gate field-effect transistor) Sensors:** A modified MOSFET-based system where only the sensing and reference electrodes contact rumen fluid. EGFET sensors simplify packaging and are better suited for rumen deployment. Recent developments include all-solid-state wireless EGFET systems for real-time monitoring [7].

These next-generation devices aim to enhance long-term stability while minimizing drift, biofouling, and energy consumption, thereby making continuous *in vivo* monitoring more reliable.

3.2 Motility sensors

Beyond physicochemical parameters, rumen function is also reflected in its mechanical activity. Rumen motility is essential for mixing digesta, facilitating microbial fermentation, and promoting eructation. Alterations in contraction frequency or strength often precede clinical signs of metabolic stress or gastrointestinal dysfunction. Modern motility sensors typically incorporate triaxial accelerometers embedded within bolus devices. These sensors detect multidirectional movement and convert mechanical contractions into electrical signals. Advanced algorithms analyze contraction patterns to differentiate normal rumination from abnormal motility associated with anorexia, ketosis, acidosis, or stress. Thus, motility monitoring complements pH and temperature data by providing a functional assessment of rumen dynamics.

3.3 Temperature sensors

Rumen temperature sensors continuously monitor internal rumen temperature, providing insight into fermentation efficiency, metabolic activity, stress, and disease conditions. Temperature fluctuations may indicate fever, heat stress, feed intake variation, or digestive disturbances. Continuous monitoring enables early health intervention and optimized feeding management.

Most rumen temperature sensors use

- **Thermistors:** Temperature-sensitive resistors whose resistance changes with temperature. Typically made of metallic oxides and encapsulated in protective materials such as epoxy or glass.
- **Thermocouples:** Devices that generate voltage proportional to temperature differences.

These sensors offer a non-invasive and reliable method for monitoring animal health.

3.4 Biomarker sensors

Monitoring ruminal biomarkers provides deeper insight into metabolic and digestive status beyond conventional parameters like pH and temperature.

Key ruminal biomarkers include

- Histamine
- Ammonia
- Lactic acid

Traditional laboratory methods for biomarker detection are expensive and unsuitable for real-time monitoring. Consequently, electrochemical sensors have emerged as promising alternatives due to their sensitivity, rapid response, and cost-effectiveness.

Types of electrochemical biomarker sensors

A) Impedimetric sensors: Measure changes in electrical impedance caused by biomarker interactions at the electrode surface. For example, reduced graphene oxide-based histamine biosensors demonstrate high sensitivity and suitable detection ranges for ruminal applications.

B) Amperometric sensors: Measure current at a constant applied potential. Often enzyme-based (*e.g.*, amine oxidases), these sensors enable selective detection of biomarkers within biologically relevant ranges.

C) Voltammetric sensors: Measure current as applied voltage varies. These sensors provide sensitive and selective detection across concentration ranges relevant to rumen physiology and are suitable for continuous monitoring.

3.5 Metabolite sensors

Moving beyond individual biomarkers, metabolite sensors focus on quantifying key fermentation end products. Volatile fatty acids (VFAs), namely acetate, propionate, and butyrate, constitute the primary energy source for ruminants and serve as direct indicators of fermentation efficiency and dietary balance.

The concentration and ratio of VFAs provide critical information about feed utilization, rumen microbial ecology, and risk of metabolic disorders. Conventional analytical methods such as gas chromatography and titration are precise but require sample collection and laboratory processing, making them unsuitable for continuous real-time monitoring. As a result, current research is increasingly directed toward developing electrochemical and microfluidic sensor platforms capable of *in situ* VFA detection, which would represent a major advancement in precision nutrition management.

3.6. Gas and redox sensors (Emerging approaches)

The rumen is also a major site of anaerobic gas production, particularly methane and carbon dioxide. Monitoring gas profiles and oxidation-reduction (redox) potential can provide valuable information about microbial activity, fermentation balance, and environmental sustainability. Although still largely in the experimental stage, integrated gas and redox sensors hold promise for linking rumen metabolism with greenhouse gas mitigation strategies.

4. Ideal characteristics of a rumen VFA sensor

For accurate and reliable detection of volatile fatty acids (VFAs) within the rumen, an ideal sensor should exhibit the following properties:

- High chemical stability to withstand the acidic and anaerobic rumen environment.
- Excellent sensitivity and selectivity toward target metabolites or biomarkers.
- Compact and ingestible design suitable for oral administration and long-term retention in the rumen.
- Compatible output signal that allows efficient data acquisition, rapid processing, and wireless transmission for real-time monitoring.

4.1 Electrochemical biosensors for VFA monitoring

Electrochemical biosensors are promising tools for real-time VFA detection due to their rapid response, sensitivity, and compatibility with miniaturized wireless systems. Recent developments in VFA sensing primarily focus on microorganism-based and enzyme-based electrochemical platforms [8].

4.1.1 Microorganism-based electrochemical biosensors

These biosensors utilize microbial metabolic activity to generate measurable electrical signals. They are broadly categorized into:

1. Microbial electrochemical sensors

These systems create a direct interface between microbial metabolism and an electrode, converting biochemical reactions into electrical signals. For instance, amperometric microbial electrodes have been developed for inline acetate detection, demonstrating good linearity and sensitivity.

2. Microbial Fuel Cells (MFCs)

MFC-based biosensors generate electrical current through microbial oxidation of substrates. They are available in:

- **Single-chamber MFCs:** Compact and promising, but may face limitations related to oxygen exposure, sensitivity, and stability.
- **Dual- and triple-chamber MFCs:** Offer improved detection performance and stability; however, their larger size limits practical rumen deployment.

Current research focuses on enhancing linearity, sensitivity, response time, and long-term stability of MFC-based VFA sensors for ruminal application.

4.1.2 Enzymatic electrochemical biosensors

Enzymatic electrochemical biosensors offer high specificity for volatile fatty acid (VFA) detection by coupling enzyme-catalyzed reactions with electrochemical signal generation [9]. The target metabolite is selectively converted into an electroactive product, commonly hydrogen peroxide (H_2O_2), which is quantified at the electrode surface, producing a signal proportional to concentration.

1. **Acetate detection:** Acetate sensing typically employs enzyme cascades such as acetate kinase, pyruvate kinase, and pyruvate oxidase immobilized on modified electrodes. These reactions ultimately generate H_2O_2 for amperometric measurement. Although analytically precise, many reported systems function optimally below the high physiological acetate concentrations found in the rumen, highlighting the need to expand their linear detection range and improve operational stability.
2. **Propionate detection:** Propionate detection has been achieved using enzyme systems such as propionate CoA transferase and short-chain acyl-CoA oxidase. These platforms demonstrate good selectivity; however, challenges remain in maintaining enzyme activity, preventing biofouling, and ensuring stable performance under ruminal conditions [10].

Overall, enzymatic biosensors provide excellent selectivity and miniaturization potential, but durability and long-term *in vivo* reliability remain key limitations.

Future challenges

Although rumen sensor technology has advanced considerably, several practical challenges remain before it can be widely adopted. Sensors must be small, safe, and durable enough to function in the harsh rumen environment without harming the animal. Ensuring long-term reliability, accurate measurements, minimal sensor drift, and efficient battery life is essential. Reliable wireless data transmission and simple, user-friendly systems that convert complex data into clear management decisions are equally important. In addition, reducing costs, meeting regulatory and animal welfare standards, ensuring data security, and providing proper

training to farmers and veterinarians are crucial for successful and sustainable implementation of rumen sensor technology.

5. Conclusion

The development of rumen sensor technology represents a major breakthrough in precision livestock management and ruminant nutrition. By enabling continuous, real-time monitoring of key ruminal parameters such as pH, metabolites, and microbial activity, these systems provide deeper insight into the complex rumen ecosystem and support data-driven decisions in feeding, health management, and herd optimization. This transition from reactive to proactive management allows early disease detection, improved nutritional precision, and more individualized animal care. Although challenges such as device durability, miniaturization, data accuracy, system integration, and cost remain, ongoing interdisciplinary innovation is steadily addressing these limitations. As the technology advances and becomes more accessible, rumen sensors have the potential to enhance animal welfare, improve feed efficiency, reduce metabolic disorders, and lower the environmental footprint of ruminant production, making them a key component of sustainable and efficient future livestock systems.

Conflict of Interest

Not available

Financial Support

Not available

References

1. Arai S, Okada H, Sawada H, Takahashi Y, Kimura K, Itoh T. Evaluation of ruminal motility in cattle by a bolus-type wireless sensor. *Journal of Veterinary Medical Science*. 2019;81(12):1835-1841.
2. Castro-Costa A, Salama AAK, Moll X, Aguiló J, Caja G. Using wireless rumen sensors for evaluating the effects of diet and ambient temperature in nonlactating dairy goats. *Journal of Dairy Science*. 2015;98(7):4646-4658.
3. Choi W, Ro Y, Kim D, Hong L, Kim D. Induction of hypocalcaemia and evaluation of reticulorumen motility using a three-axis accelerometer. *Animal Production Science*. 2022;62(5):409-415.
4. Dijkstra J, Van Gastelen S, Dieho K, Nichols K, Bannink A. Rumen sensors: Data and interpretation for key rumen metabolic processes. *Animal*. 2020;14(S1):S176-S186.
5. Fromm K, Ammon C, Amon T, Hoffmann G. Evaluating reticulorumen temperature, rumination, activity and pH measured by rumen sensors as indicators of heat load in fattening bulls. *Sensors*. 2025;25(20):6401.
6. Hajnal É, Kovács L, Vakulya G. Dairy cattle rumen bolus developments with special regard to the applicable artificial intelligence methods. *Sensors*. 2022;22(18):6812.
7. Han CS, Kaur U, Bai H, Dos Reis BR, White R, Nawrocki RA, *et al*. Invited review: Sensor technologies for real-time monitoring of the rumen environment. *Journal of Dairy Science*. 2022;105(8):6379-6404.
8. Lee M, Seo S. Wearable wireless biosensor technology for monitoring cattle: A review. *Animals*. 2021;11(10):2779.

9. Lin X, Pacheco D, Kemp PD, Waghorn GC, Cosgrove GP. Evaluation of sensors for monitoring rumen pH, temperature and pressure. Proceedings of the New Zealand Society of Animal Production. 2010;70:5-10.
10. Vakulya G, Hajnal É, Udvardy P, Simon G. In-depth development of a versatile rumen bolus sensor for dairy cattle. Sensors. 2024;24(21):6976.

How to Cite This Article

Shinde K, Muquit SP, Kale C. Advances in rumen sensors for real time assessment of metabolic processes. International Journal of Veterinary Sciences and Animal Husbandry. 2026;11(2):360-364.

Creative Commons (CC) License

This is an open-access journal, and articles are distributed under the terms of the Creative Commons Attribution-Non Commercial-Share Alike 4.0 International (CC BY-NC-SA 4.0) License, which allows others to remix, tweak, and build upon the work non-commercially, as long as appropriate credit is given and the new creations are licensed under the identical terms.