



ISSN Print: 2664-844X
 ISSN Online: 2664-8458
 NAAS Rating (2026): 4.97
 IJAFS 2026; 8(9): 813-821
www.agriculturaljournals.com
 Received: 15-06-2026
 Accepted: 13-08-2026
 Published: 24-09-2026

RG Jathar

M.Tech. Research Scholar,
 Department of Farm
 Machinery and Power
 Engineering, Dr. ASCAET,
 MPKV Rahuri,
 Maharashtra, India.

AA Walunj

Assistant Professor,
 Department of Farm
 Machinery and Power
 Engineering, Dr. ASCAET,
 MPKV Rahuri,
 Maharashtra, India.

SM Nalawade

Professor and Head,
 Department of Farm
 Machinery and Power
 Engineering, Dr. ASCAET,
 MPKV Rahuri,
 Maharashtra, India.

PB Kadam

Associate Professor,
 Department of Farm
 Machinery and Power
 Engineering, Dr. ASCAET,
 MPKV Rahuri,
 Maharashtra, India.

Corresponding Author:

RG Jathar

M.Tech. Research Scholar,
 Department of Farm
 Machinery and Power
 Engineering, Dr. ASCAET,
 MPKV Rahuri,
 Maharashtra, India.

A review: Study of the different types of metering mechanism used in seed drill and planter

RG Jathar¹, AA Walunj², SM Nalawade³, PB Kadam⁴

DOI: <https://www.doi.org/10.33545/2664844X.2026.v8.i9k.1958>

ABSTRACT

Precision seed placement plays a vital role in achieving optimum crop establishment, efficient utilization of agricultural inputs, and higher crop productivity. The performance of seed drills and planters largely depends on the seed metering mechanism, which regulates the discharge of seeds at the desired rate and spacing. Uniform seed distribution minimizes intra-row competition and improves germination, emergence, and crop growth. In recent years, seed metering technology has evolved from conventional mechanical devices to advanced pneumatic, electronic, and mechatronic systems integrated with sensors and intelligent control units.

This review summarizes the different types of seed metering mechanisms used in seed drills and planters, including mechanical, pneumatic, electronic/mechatronic, controlled, and crop-specific systems. Their constructional features, operating principles, technical specifications, performance indices, advantages, limitations, and applications reported in the literature are discussed. A comparative assessment of different metering mechanisms based on seed spacing accuracy, operating speed, power requirement, adaptability, and automation level is also presented. The review highlights recent developments in electrically driven and sensor-based metering systems for precision agriculture and identifies future research directions toward intelligent, energy-efficient, and high-speed seed metering technologies.

Keywords: Seed metering mechanism, Seed drill, Precision planter, Mechanical seed metering, Pneumatic seed metering, Vacuum disc meter, Electronic and mechatronic systems, Seed singulation, Seed spacing uniformity, Quality Feed Index, Variable-rate seeding, Precision agriculture

1. Introduction

Mechanized sowing is one of the most important field operations affecting crop establishment and final yield. Seed drills and precision planters are designed to meter seeds uniformly, place them at the desired depth, maintain proper seed-to-seed spacing, and ensure adequate soil coverage for better germination and emergence. The performance of these machines is primarily governed by the seed metering mechanism, which controls the quantity and uniformity of seed delivery (Wang *et al.*, 2023).


The seed metering mechanism is considered the heart of a planter because it directly influences plant population, spacing uniformity, and crop productivity. The efficiency of a metering system is commonly evaluated using parameters such as Quality Feed Index (QFI), Miss Index, Multiple Index, and Precision Index. A well-designed metering mechanism reduces seed wastage, minimizes plant competition, and improves resource utilization (Karayel *et al.*, 2004).

Conventional seed drills mainly employ mechanical metering mechanisms such as fluted rollers, internal double-run feed, cup feed, cell feed, and plate-type meters because of their simple construction, low manufacturing cost, and ease of maintenance. However, these mechanisms are generally suitable for continuous seed flow and exhibit limitations in precision planting due to seed damage, multiple seed drops, and sensitivity to ground wheel slip.

To overcome these limitations, pneumatic seed metering systems were developed. Vacuum and positive-pressure metering mechanisms provide better seed singulation, higher planting accuracy, and improved adaptability to different seed sizes and shapes. Recent advancements have further integrated electric drives, microcontrollers, sensors, and closed-loop control systems into conventional planters, enabling variable-rate seeding and precision planting under varying field conditions (Pareek *et al.*, 2025).

This review presents a concise overview of the different seed metering mechanisms reported in the literature. Their working principles, technical specifications, performance characteristics, advantages, limitations, and recent technological developments are comparatively discussed to provide a comprehensive understanding of modern seed metering technologies.

Seed Metering Mechanisms		Mechanical		Fluted Roller		Internal Double Run	
Cup Feed		Cell Feed		Plate Type		Belt Type	
						Pneumatic	
						Vacuum Disc	



Flowchart 1. Classification of seed metering mechanisms used in seed drills and precision planters.

2. Performance indices and evaluation criteria

The performance of a seed metering mechanism is evaluated based on its ability to deliver seeds uniformly at the desired spacing with minimum misses and multiple seed drops. Standardized performance indices, as recommended in ISO 7256-1, are widely used to compare the effectiveness of different seed metering systems. These indices provide a quantitative assessment of seed spacing uniformity and planting precision (Karayel *et al.*, 2004).

The most commonly used performance indices are Quality Feed Index (QFI), Miss Index (MI), Multiple Index (MUI), and Precision Index (PI). These parameters are determined from the measured seed spacing under laboratory or field conditions and are extensively reported in the literature for evaluating seed drills and precision planters.

2.1 Quality Feed Index (QFI)

The Quality Feed Index (QFI) represents the percentage of seed spacings that fall within 0.5 to 1.5 times the theoretical seed spacing. It indicates the ability of the metering mechanism to deliver single seeds at the desired interval.

A higher QFI indicates better seed singulation and more uniform seed placement. Precision pneumatic and electronically controlled planters generally achieve QFI values above 90–95%, whereas conventional mechanical metering systems usually exhibit comparatively lower values depending on operating conditions (Karayel, 2009).

2.2 Miss Index (MI)

The Miss Index (MI) is the percentage of seed spacings greater than 1.5 times the theoretical spacing, indicating that one or more seeds were not delivered at the desired location.

A lower miss index is desirable because it ensures proper plant population and minimizes gaps within the crop row. Miss index generally increases with higher forward speed, poor seed singulation, and improper adjustment of the metering mechanism (Karayel, 2009).

2.3 Multiple Index (MUI)

The Multiple Index (MUI) represents the percentage of seed spacings less than 0.5 times the theoretical spacing, indicating that two or more seeds were dropped together.

Lower MUI values indicate better singulation performance and reduced competition among adjacent plants. Multiple seed drops are influenced by seed shape, metering plate design, operating speed, and vacuum pressure in pneumatic systems.

2.4 Precision Index (PI)

The Precision Index (PI) measures the variation in acceptable seed spacings and is expressed as the coefficient of variation of the seed spacing distribution. It reflects the consistency of seed placement during planting.

Lower PI values indicate better spacing uniformity and higher planting precision. Electronic and mechatronic seed metering systems generally produce lower precision index values than conventional me-

chanically driven systems because they minimize errors caused by ground wheel slip and transmission vibration (Karayel, 2009).

Table 1. Performance indices commonly used for evaluation of seed metering mechanisms.


Performance Index	Purpose	Desired Value
Quality Feed Index (QFI)	Indicates percentage of correctly spaced seeds	Higher (> 90–95%)
Miss Index (MI)	Indicates missed seed placements	Lower (< 5%)
Multiple Index (MUI)	Indicates multiple seed drops	Lower (< 5%)
Precision Index (PI)	Indicates spacing uniformity	Lower (< 15–20%)

Among the performance indices, Quality Feed Index is the most widely used parameter for evaluating the overall performance of seed metering mechanisms because it directly reflects seed spacing accuracy. The Miss Index and Multiple Index indicate planting errors due to missed or multiple seed drops, while the Precision Index measures the consistency of seed placement. Collectively, these indices provide a reliable basis for comparing different metering mechanisms under laboratory and field conditions. Studies reviewed in this paper show that pneumatic and electronically controlled seed metering systems generally achieve higher QFI and lower MI, MUI, and PI values than conventional mechanical systems, demonstrating their superior precision in seed placement.

3. Mechanical seed metering mechanisms

Mechanical seed metering mechanisms are the most widely used seed metering devices in conventional seed drills and planters due to their simple construction, low manufacturing cost, ease of operation, and minimum power requirement. These mechanisms meter seeds through mechanical movement of rollers, plates, cups, cells, or belts driven by the ground wheel or transmission shaft. They are suitable for a wide range of cereal and pulse crops; however, their precision is generally lower than pneumatic and electronically controlled systems because of ground wheel slip, vibration, and limited seed singulation capability (Yitao *et al.*, 2017).

Mechanical metering mechanisms can be classified into different types based on their method of seed pickup and delivery, as shown in Flowchart 2.



Flowchart 2. Classification of Mechanical Seed Metering Mechanisms

3.1 Fluted feed roller mechanism

Construction and Working Principle

The fluted roller is the most commonly used seed metering mechanism in seed drills. It consists of a fluted roller mounted below the seed hopper, an adjustable gate, feed cup, and cut-off device. As the roller rotates, seeds fill the longitudinal flutes and are discharged into the seed tube. Seed rate is controlled by changing the exposed flute length or the rotational speed of the roller (Yitao *et al.*, 2017).




Figure 1. Fluted Roller

Advantages

- Simple and economical construction
- Easy seed rate adjustment
- Suitable for cereals and fertilizers
- Low power requirement
- Easy maintenance

Limitations

- Continuous seed flow without singulation
- Poor spacing uniformity
- Output affected by seed properties and ground wheel slip
- Not suitable for precision planting

Table 2. Typical Technical Specifications

Parameter	Typical Range
Roller diameter	40–60 mm
Number of flutes	10–16
Flute depth	5–12 mm
Roller speed	30–50 rpm
Working length	20–50 mm

3.2 Internal double-run feed mechanism

The internal double-run feed mechanism consists of a double-faced feed wheel having coarse and fine ribs for handling different seed sizes. The seed rate is adjusted by changing the rotational speed of the feed wheel. Compared with the fluted roller, it offers better adaptability for different crops but still operates as a continuous-flow metering mechanism.

Advantages

- Suitable for both small and large seeds
- Positive seed delivery
- Simple construction

Limitations

- Bulk seed delivery
- Mechanical adjustment required
- Lower precision compared with pneumatic systems

3.3 Cup feed and cell feed mechanisms

Cup feed mechanisms use cups mounted on the periphery of a rotating disc to pick seeds from the hopper and release them into the seed tube. Cell feed mechanisms use equally spaced cells on a rotating wheel for seed pickup and delivery.

These mechanisms are mainly employed for medium and large seeds and provide better seed handling than continuous-flow mechanisms. However, precision decreases at higher operating speeds.

3.4 Plate-type metering mechanisms

Plate-type metering mechanisms are among the earliest precision seed meters and are widely used in row crop planters. Based on the orientation of the seed plate, they are classified into:

- Horizontal plate
- Inclined plate
- Vertical plate

The plate contains uniformly spaced cells that pick individual seeds and release them into the seed tube. Seed spacing depends on plate design, cell size, rotational speed, and forward speed.






Figure 2. Cup Feed **Figure 3.** Cell Feed

**Table 3.** Typical Specifications

Parameter	Typical Value
Plate diameter	150–250 mm
Number of cells	20–40
Plate speed	15–25 rpm
Operating speed	4–6 km h ⁻¹

Advantages


- Better singulation than fluted rollers
- Low power requirement
- Simple transmission
- Plates can be replaced for different crops

Limitations

- Plate replacement required for different seed sizes
- Reduced performance at higher forward speeds
- Affected by vibration and ground wheel slip

3.5 Belt-type metering mechanism

The belt-type mechanism uses a rubber belt containing equally spaced holes corresponding to the seed size. Seeds are picked by the holes and transported to the discharge point. Compared with plate-type mechanisms, belt meters provide smoother seed handling and lower seed damage, making them suitable for fragile seeds.

**Figure 5.** Belt type

Mechanical seed metering mechanisms continue to be widely used because of their simple construction, low cost, and ease of maintenance. Among these, fluted roller and internal double-run mechanisms are suitable for continuous seeding operations in cereals, whereas plate-type and belt-type mechanisms provide better seed singulation for row crops such as maize, cotton, and soybean. However, all mechanically driven systems are affected by ground wheel slip, vibration, and limited adaptability at higher operating speeds. Consequently, pneumatic and electronically controlled metering systems have been increasingly adopted for precision planting applications.

Table 4. Comparison of Mechanical Seed Metering Mechanisms

Mechanism	Suitable Crops	Precision	Seed Damage	Cost	Application
Fluted Roller	Wheat, soybean, pulses	Low	Low	Low	Seed drills
Internal Double Run	Cereals	Low–Moderate	Low	Low	Seed drills
Cup Feed	Medium-sized seeds	Moderate	Low	Moderate	Conventional planters
Cell Feed	Pulses, cereals	Moderate	Low	Moderate	Seed drills
Plate Type	Maize, cotton, groundnut	High	Moderate	Moderate	Precision planters
Belt Type	Cotton, soybean	High	Very Low	Moderate	Precision planters

4. Pneumatic seed metering mechanisms

Pneumatic seed metering mechanisms have become the preferred choice for precision planting because of their superior seed singulation, high planting accuracy, and ability to handle seeds of different sizes and shapes. Unlike mechanical meters, pneumatic systems use negative or positive air pressure to pick, hold, and release individual seeds, thereby reducing seed damage and improving spacing uniformity. These systems are widely used in precision planters for crops such as maize, cotton, soybean, sunflower, and rapeseed (Huang *et al.*, 2018).

Pneumatic Seed Metering Mechanisms | — Vacuum (Negative Pressure) | — Vacuum Disc | — Standard Vacuum Plate |

— Flexible Orifice | — Positive Pressure | — Air Blowing
— Centralized Pneumatic

Flowchart 3. Classification of Pneumatic Seed Metering Mechanisms**4.1 Vacuum disc (negative pressure) meter****Working Principle**

The vacuum disc seed meter consists of a perforated seed disc rotating inside a sealed housing connected to a vacuum source. As the disc rotates through the seed chamber, negative pressure holds a single seed over each orifice. A singulator removes extra seeds, and the seed is released into the seed tube when the vacuum is interrupted at the discharge point (Huang *et al.*, 2018).




Figure 6. Pneumatic seed metering device (Xiaojun Gao *et al.*, 2023) [1]

Vacuum pressure, orifice diameter, disc speed, and seed properties are the major factors affecting metering performance.

Table 5. Typical Technical Specifications

Parameter	Typical Range
Vacuum pressure	2–4 kPa
Orifice diameter	2.5–3.0 mm
Disc peripheral speed	0.42–0.50 m s ⁻¹
Operating speed	4–15 km h ⁻¹
Quality Feed Index	93–97%

Advantages

- Excellent seed singulation
- Suitable for irregular-shaped seeds
- High planting accuracy
- Reduced seed damage
- Compatible with electronic drive systems

Limitations

- Higher power requirement
- Requires blower or vacuum pump
- Sensitive to dust leakage and poor sealing
- Higher manufacturing cost

4.2 Centralized pneumatic metering system

Centralized pneumatic systems meter seeds at a central location and distribute them to individual rows using air streams. These systems improve uniformity among rows while reducing the number of individual metering units.

Studies on rapeseed reported qualified seed indices above 86% with coefficients of variation below 5% under optimized operating conditions, indicating satisfactory planting performance (Yitao *et al.*, 2017).

4.3 Factors affecting pneumatic meter performance

The performance of pneumatic seed meters depends on several operating and design parameters, including:

- Vacuum pressure
- Orifice diameter
- Disc rotational speed
- Forward speed
- Seed size and shape
- Seed moisture content
- Singulator adjustment

Proper optimization of these parameters improves seed pickup, reduces missed and multiple seed drops, and enhances spacing uniformity.

Table 6. Typical Operating Parameters Reported for Pneumatic Seed Meters

Crop	Vacuum Pressure	Orifice Size	Operating Speed	QFI
Cotton	2.0 kPa	2.5 mm	0.42 m s ⁻¹	94.7%
Cotton (Optimized)	3.96 kPa	2.95 mm	4.26 km h ⁻¹	93%
Flexible Orifice	3.40 kPa	3.0 mm	4.67 km h ⁻¹	97.3%
Rapeseed	–1600 Pa	—	16 rpm	92.5%

(continued on next page)

4.4 Instrumentation used in the reviewed studies

Several studies incorporated specialized instrumentation to evaluate the performance of pneumatic seed metering mechanisms.

Table 7. Instrumentation Used in the Reviewed Studies

Instrument	Purpose
Vacuum pump	Generates negative pressure
Pressure regulator	Controls vacuum level
Vacuum gauge	Measures vacuum pressure
Electric motor	Drives seed metering disc
Photoelectric sensor	Detects seed passage
Radar speed sensor	Measures forward speed
Microcontroller	Controls metering operation
Motor controller	Regulates motor speed

Pneumatic seed metering mechanisms provide significantly better seed placement accuracy than conventional mechanical systems. The reviewed studies consistently reported Quality Feed Index values above 90%, low miss indices, and reduced multiple seed drops under optimized operating conditions. Their ability to handle different seed sizes without extensive grading makes them suitable for precision planting of row crops. However, the requirement for vacuum generation, precise sealing, and additional electronic components increases both system complexity and cost. Despite these limitations, pneumatic metering technology remains the benchmark for modern high-speed precision planters due to its superior planting accuracy and adaptability.

5. Electronic and mechatronic seed metering systems

Electronic and mechatronic seed metering systems have been developed to overcome the limitations of conventional ground wheel-driven planters, such as wheel slip, transmission losses, vibration, and difficulty in adjusting seed rate. These systems replace the mechanical transmission with electrically driven metering units integrated with

sensors, controllers, and actuators, enabling accurate seed placement and real-time control (Pareek *et al.*, 2025).

Unlike conventional systems, electronically controlled planters allow independent control of each row unit, improve spacing uniformity, and facilitate variable-rate seeding for precision agriculture.

5.1 Electric drive systems

Electric drive systems use electric motors to drive the seed metering mechanism instead of ground wheel transmission. Depending on the planter design, the electric drive may either replace only the transmission system or function as a completely integrated seed metering unit (Minfeng *et al.*, 2018).

Studies reported that electric-driven precision planters achieved a qualified seed spacing greater than 95% at forward speeds ranging from 5 to 13 km h⁻¹. The elimination of ground wheel slip significantly improved seed spacing uniformity under field conditions (Pareek *et al.*, 2025).

5.2 Instrumentation and control components

Electronic seed metering systems integrate several control and sensing components to regulate the metering process.

Table 8. Major components used in electronic seed metering systems.

Component	Function
DC servo motor	Drives the seed metering unit
BLDC motor	Provides smooth and efficient metering
Motor controller	Regulates motor speed
Microcontroller	Controls metering operation
Relay module	Controls power supply to actuators
Radar speed sensor	Measures forward speed
Rotary encoder	Measures shaft speed and position
Photoelectric sensor	Detects seed flow and missed seeds
12 V battery	Power source for the system




Figure 7. Schematic diagram of embedded mechatronic seed metering control system. (Pareek *et al.*, 2025).

These components operate together to maintain synchronization between planter forward speed and seed metering speed, thereby improving planting accuracy.

5.3 Performance and advantages

Research demonstrated that replacing the conventional mechanical drive with an electronic drive improved planting performance. Laboratory and field evaluations reported an increase in the Quality Feed Index by approximately 2.5% and a reduction in the Precision Index due to improved speed control and reduced transmission vibration (Karayel *et al.*, 2004).

Advantages

- Eliminates ground wheel slip
- Improves seed spacing uniformity
- Enables real-time seed rate adjustment
- Suitable for variable-rate seeding
- Independent row control
- Reduced vibration
- Faster calibration

Limitations

- Higher initial investment
- Greater system complexity
- Dependence on electrical power
- Requires periodic maintenance of electronic components
- Troubleshooting requires technical expertise

5.4 Comparison of mechanical and electronic drive systems

Table 9. Mechanical vs Electronic drive systems.

Parameter	Mechanical Drive	Electronic Drive
Drive source	Ground wheel	Electric motor
Speed control	Mechanical transmission	Electronic controller
Wheel slip effect	High	Negligible
Variable-rate seeding	Not possible	Possible
Calibration	Manual	Easy and quick
Planting accuracy	Moderate	High
Maintenance	Simple	Moderate
Automation	Low	High

Electronic and mechatronic seed metering systems represent a significant advancement over conventional mechanical drives by eliminating errors caused by ground wheel slip and transmission vibration. The integration of electric motors, sensors, and embedded controllers enables precise synchronization between planter speed and seed metering rate, resulting in improved seed spacing uniformity. Although these systems involve higher initial cost and greater technical complexity, their ability to support precision agriculture practices such as variable-rate seeding and real-time monitoring makes them highly suitable for modern farming systems.

6. Controlled and intelligent seed metering systems

The advancement of precision agriculture has led to the development of controlled and intelligent seed metering systems capable of adjusting seed rate according to field variability. These systems integrate electronic controllers, positioning technologies, sensors, and variable-rate algorithms to achieve accurate seed placement and optimum plant population. Compared with conventional planters, intelligent metering systems improve input-use efficiency, reduce operational cost, and enhance crop productivity (Yang *et al.*, 2016).

6.1 Variable Rate Technology (VRT)

Variable Rate Technology (VRT) is a precision farming approach that allows the seed application rate to vary according to soil properties, crop requirements, and field conditions. Unlike conventional uniform seeding, VRT enables optimum plant population by applying different seed rates within different management zones of the same field (Zhang *et al.*, 2021) [2].

The adoption of VRT has increased significantly due to the availability of GPS technology, electronic controllers, sensors, and digital prescription maps. According to the USDA Agricultural Resource Management Survey, the use of VRT for seeding operations has increased considerably in recent years (Yang *et al.*, 2016).

6.2 Approaches used in variable rate seeding

Variable-rate seeding is generally implemented using two approaches:

(a) Map-Based Variable Rate Seeding

In this approach, prescription maps are prepared using previously collected field information such as soil characteristics, yield maps, remote sensing data, or drone imagery. The controller continuously adjusts the seed rate according to the predefined prescription map during planting.

(b) Sensor-Based Variable Rate Seeding

Sensor-based systems determine field conditions in real time using sensors such as soil moisture sensors, electrical conductivity sensors, or crop sensors. Based on sensor inputs, the controller automatically adjusts the seed metering rate without requiring pre-prepared prescription maps (Yang *et al.*, 2016).

Variable Rate Seeding | — Map-Based Approach | —
 Prescription Map | — GPS | — Controller → Variable Seed Rate
 — Sensor-Based Approach | — Real-time Sensors | —
 Controller | — Variable Seed Rate

Flowchart 4. Types of Variable Rate Seeding

6.3 Multi-hybrid planting systems

Recent intelligent planters are capable of planting multiple hybrids within the same field by using electronically controlled metering units and divided seed hoppers. These systems automatically switch between hybrids while maintaining the desired seed spacing and planting depth.

Studies reported successful operation of multi-hybrid planting systems at planting speeds ranging from 9.6 to 11.6 km h⁻¹, demonstrating their suitability for high-speed precision planting (Precision Planting LLC, 2022) [3].

Table 10. Comparison of Conventional and Intelligent Seed Metering Systems

Parameter	Conventional System	Intelligent System
Seed Rate	Fixed	Variable
Controller	Mechanical	Electronic
GPS Integration	No	Yes
Sensor Integration	No	Yes
Prescription Map	Not applicable	Applicable
Automation	Low	High
Precision	Moderate	High
Input Efficiency	Moderate	High

Advantages

- Improves seed placement accuracy.
- Optimizes plant population according to field variability.
- Reduces seed wastage and production cost.
- Enables site-specific crop management.
- Supports precision agriculture practices.
- Increases resource-use efficiency.

Limitations

- Higher initial investment.
- Requires GPS, sensors, and electronic controllers.
- Depends on accurate field data and prescription maps.
- Greater technical knowledge is required for operation.

Controlled and intelligent seed metering systems represent the latest advancement in precision planting technology. By integrating GPS, sensors, electronic controllers, and Variable Rate Technology, these systems can adjust seed application according to spatial field variability, resulting in improved crop establishment and better utilization of inputs. Compared with conventional planters, intelligent systems provide greater flexibility, higher planting precision, and better resource-use efficiency. However, their widespread adoption is still constrained by higher investment costs and the need for advanced technical expertise. Continuous improvements in digital agriculture and automation are expected to make these technologies more accessible and economically viable in future precision farming systems.

7. Crop-specific applications of seed metering mechanisms

Different crops require different seed metering mechanisms because of variations in seed size, shape, weight, and physical properties. Therefore, the design and operating parameters of the metering mechanism should be selected according to the engineering properties of the seed to achieve uniform seed spacing, minimum seed damage, and high planting precision.

The reviewed studies indicate that mechanical metering mechanisms are generally suitable for cereals and pulse crops, whereas pneumatic and electronically controlled systems are preferred for precision planting of row crops such as maize, cotton, soybean, and rapeseed.

7.1 Maize

Maize is one of the most extensively studied crops for precision planting due to its relatively large seed size and requirement for uniform plant spacing. Researchers optimized the structural parameters of me-

chanical precision metering devices to improve seed filling and singulation under high-speed operation. The optimum operating conditions included a seed barrier opening height of 19.4 mm, grooved tooth depth of 1.2 mm, and operating speed of 10.7 km h⁻¹, resulting in a qualified seed spacing above 95% (Dabbaghi *et al.*, 2010).

7.2 Cotton

Vacuum disc metering mechanisms are widely adopted for cotton because they provide excellent seed singulation with minimum seed damage. Studies reported that vacuum pressure between 2.0 and 4.0 kPa and an orifice diameter of approximately 2.5–3.0 mm produced optimum planting performance. Under optimized operating conditions, the Quality Feed Index exceeded 93%, while Miss Index and Multiple Index remained below 5% (Huang *et al.*, 2018).

7.3 Soybean

Soybean planting requires accurate seed spacing while minimizing mechanical damage. Vacuum seed metering systems demonstrated superior performance compared with conventional mechanical drills by improving seed spacing uniformity and crop emergence. Laboratory and field evaluations indicated acceptable precision at forward speeds of 1.0–1.5 m s⁻¹, particularly when combined with double-disc furrow openers (Barut *et al.*, 2006) [4].

7.4 Multi-crop planters

Modern multi-crop planters are designed to accommodate seeds of different sizes by modifying the metering cell dimensions and exposure length. Seeds are generally classified into large, medium, and small categories based on their geometric mean diameter. Laboratory studies reported cell filling above 98% and seed damage below 0.5%, while field evaluations achieved Quality Feed Index values around 94%, demonstrating satisfactory performance for multi-crop planting applications (Dabbaghi *et al.*, 2010).

Table 11. Summary of crop-specific seed metering mechanisms.

Crop	Preferred Metering Mechanism	Important Operating Parameters	Reported Performance
Maize	Mechanical Plate / Pneumatic Vacuum	10.7 km h ⁻¹ , 19.4 mm barrier opening	Qualified spacing > 95%
Cotton	Vacuum Disc	2–4 kPa vacuum, 2.5–3.0 mm orifice	QFI > 93%
Soybean	Vacuum Meter	1.0–1.5 m s ⁻¹ forward speed	Improved spacing uniformity
Rapeseed	Centralized Pneumatic	16 rpm, –1600 Pa	Qualified index > 92%
Multi-crop	Cell-type Meter	Cell size based on seed dimensions	Cell filling > 98%

The literature demonstrates that the selection of a seed metering mechanism should be based on crop characteristics and planting requirements. Mechanical metering systems are economical and suitable for cereal crops where continuous seed flow is acceptable. Pneumatic vacuum meters provide superior seed singulation and spacing accuracy for row crops such as maize, cotton, and soybean, particularly at higher operating speeds. Multi-crop metering systems offer greater flexibility by accommodating different seed sizes with minimal seed damage, making them suitable for diversified farming systems. Overall, matching the metering mechanism with the physical properties of the seed is essential for achieving optimum planting performance.

8. Comparative analysis and future prospects

The evolution of seed metering mechanisms has significantly improved planting precision, operational efficiency, and crop establishment. Conventional mechanical metering systems continue to be widely used because of their simple construction, low manufacturing

cost, and ease of maintenance. However, their performance is affected by ground wheel slip, transmission losses, and limited seed singulation, making them less suitable for high-speed precision planting.

Pneumatic seed metering mechanisms have overcome many of these limitations by using vacuum or positive air pressure for seed pickup and release. These systems provide superior seed singulation, lower miss and multiple indices, and better adaptability to different seed sizes and shapes. The literature reviewed in this study consistently reported Quality Feed Index values above 90% for properly optimized pneumatic metering systems.

The integration of electric drives, microcontrollers, sensors, and embedded controllers has further improved planting accuracy by eliminating mechanical transmission errors. Electronic and mechatronic systems enable independent row control, real-time monitoring, and variable-rate seeding, making them suitable for modern precision agriculture. Although these systems require higher initial investment and technical expertise, they offer greater flexibility and improved planting performance.

Table 12. Comparative evaluation of different seed metering mechanisms.

Parameter	Mechanical	Pneumatic	Electronic / Mechatronic
Working Principle	Mechanical feed	Air pressure/vacuum	Motor-driven with electronic control
Seed Singulation	Low–Moderate	High	Very High
Quality Feed Index	82–90%	90–98%	92–98%*
Operating Speed	3–8 km h ⁻¹	5–15 km h ⁻¹	5–13 km h ⁻¹
Power Requirement	Low	High	Moderate
Seed Damage	Moderate	Low	Low
Variable Rate Seeding	Not available	Limited	Available
Automation Level	Low	Moderate	High
Initial Cost	Low	High	High
Maintenance	Simple	Moderate	Moderate–High

*Reported values depend on the base metering mechanism and control strategy.

Key findings from the reviewed literature

- Mechanical metering mechanisms remain suitable for conventional seed drills because of their low cost and simple operation.
- Plate-type and belt-type mechanisms provide better seed singulation than fluted roller mechanisms.
- Pneumatic vacuum systems consistently achieve higher seed spacing accuracy and lower miss and multiple indices than mechanical systems.
- Electronic drive systems improve planting precision by eliminating errors caused by ground wheel slip and mechanical transmission.
- Variable Rate Technology enables site-specific seed application, improving input-use efficiency and supporting precision farming practices.

Future prospects

Future research on seed metering mechanisms should focus on:

- Development of cost-effective electronic metering systems for small and medium-sized farms.
- Improvement of high-speed precision planting while maintaining seed spacing accuracy.
- Better integration of sensors, GPS, and Variable Rate Technology for real-time control.
- Optimization of pneumatic systems to reduce energy consumption while maintaining high precision.
- Development of intelligent control algorithms for automatic calibration and monitoring of seed metering performance.

The reviewed studies indicate that no single seed metering mechanism is universally suitable for all crops and operating conditions. Mechanical systems continue to be preferred for conventional cereal planting because of their simplicity and affordability, whereas pneumatic systems have become the standard for precision planting of row crops due to their superior seed singulation and spacing accuracy. The emergence of electronically controlled metering systems represents a major advancement in precision agriculture by enabling closed-loop control, variable-rate seeding, and improved operational efficiency. Future developments are expected to focus on intelligent, energy-efficient, and economically viable metering technologies capable of meeting the increasing demand for sustainable agricultural production.

References

1. <https://doi.org/10.3965/j.ijabe.20160901.2285>.
2. Zhang, Q., Wang, C., & Li, H. (2021). Advances in variable rate technology for precision agriculture: A review. *Computers and Electronics in Agriculture*, 189, 106387.

3. Precision Planting LLC. (2022). Multi-hybrid planting systems and SpeedTube technology performance report. Precision Planting Technical Bulletin.
4. Barut ZB, Karayel D. Performance of a precision vacuum seeder for cotton and soybean planting. *Biosystems Engineering*. 2006;95(4):561–567.
5. Anselin L, *et al.* Site-specific management strategies for optimizing seeding rates and profitability. *Precision Agriculture*. 2013;14(5):472–489.
6. Colaço AF, Molin JP. Variable rate fertilization and seeding: Economic and environmental impacts. *Precision Agriculture*. 2017;18(3):386–404.
7. <https://doi.org/10.1016/j.ifacol.2018.08.161>
8. Precision Planting LLC. Multi-hybrid planting systems and SpeedTube technology performance report. Precision Planting Technical Bulletin. 2022.
9. <https://doi.org/10.1016/j.biosystemseng.2005.07.003>
10. <https://doi.org/10.1016/j.ifacol.2018.08.161>
11. <https://doi.org/10.1016/j.biosystemseng.2005.07.003>
12. Soyoyo BO. Design and evaluation of a motorized multi-grain crop planter. *CIGR Journal*. 2020;22(1):56–64.
13. Srivastava AK, Goering CE, Rohrbach RP, Buckmaster DR. Crop planting. In *Engineering Principles of Agricultural Machines*. ASABE. 2006:231–268.
14. Tamil Nadu Agricultural University. FMP 211 – Lecture 08: Sowing Methods – Seed Metering Mechanism. e-AGRI Course Materials.
15. USDA. Agricultural Resource Management Survey – Precision Agriculture Technologies Adoption Report. 2023.
16. Virk S. Electric drives for seed metering on row crop planters. Alabama Cooperative Extension System, ANR-3175. 2025.
17. <https://doi.org/10.3390/agriculture13071400>.
18. Gao X, *et al.* Design and validation of a centrifugal variable diameter pneumatic high-speed precision seed metering device for maize. *Biosystems Engineering*. 2023;227:161–181.
19. <https://doi.org/10.1016/j.measurement.2014.06.013>.
20. <https://doi.org/10.3965/j.ijabe.20171002.2061>.
21. Zhang Q, Wang C, Li H. Advances in variable rate technology for precision agriculture: A review. *Computers and Electronics in Agriculture*. 2021;189:106387.

How to cite this article: Jathar R, Walunj A, Nalawade S, Kadam P. A review: Study of the different types of metering mechanism used in seed drill and planter. *International Journal of Agriculture and Food Science*. 2026;8(9):813–821. doi: <https://www.doi.org/10.33545/2664844X.2026.v8.i9k.1958>